



CORDLESS
STRIP NAILER 3 1/2"
30 - 34 DEGREE
 FSN33-90 BC



MANY BRANDS
ONE BATTERY SYSTEM

This product is compatible with all 18 V battery packs and chargers within the CAS system.
cordless-alliance-system.com

BENEFITS FOR PROFESSIONALS

- + Precise fastening with high driving power
- + Tool-free depth adjustment
- + Belt hook for convenient carrying
- + Dry Fire Lock
- + No cables, no hoses – complete freedom of movement
- + No gas, no follow-up costs
- + Low maintenance
- + Firing speed of 3 shots per second for efficient operation



DESCRIPTION

The BECK 30 - 34° Cordless Framing Nailer combines the full power of a pneumatic nailer with the freedom of cordless hand tools. Ideal for demanding applications in timber and interior construction, it enables fast, powerful, and precise fastening with maximum freedom of movement. Its robust design, high driving power, and compatibility with CAS batteries make it a reliable tool for professional craftsmen who value performance, flexibility, and efficiency.

CONTACT & SERVICE

Our customer service is happy to assist you.

P +1 800 239 8665 | F +1 256 381 6659
sales.us@beck-fastening.com
beck-fastening.com

BECK AMERICA
 105 Industrial Drive
 Muscle Shoals, AL
 35661 | USA

Follow us



TOOL SPECIFICATIONS

MAGAZINE TYPE	Strips
MAGAZINE CAPACITY	57 Nails
BATTERY COMPATIBILITY	CAS 18 V LiHD 4.0 Ah
SHOTS / SECOND	2 – 3
SHOTS / BATTERY CAPACITY	600 (4 Ah)
ACTUATION SYSTEM	Single Sequential Actuation
BATTERY VOLTAGE	18 V
COLLATION DEGREE	33°
FASTENER TYPE	Paper Tape Clipped Head Nails, Plastic Strip Nails, SCRAIL® CHIPBOARD, SCRAIL® SPLITLESS
LOADING	Rear Loading
DEPTH ADJUSTMENT	Yes
BELT HOOK	Yes
INCLUDED	Tool, CAS Battery, Charger, Belt Hook, and Carrying Case
WEIGHT	9.85 lbs 4.47 kg

FASTENER CHARACTERISTICS

NAILS	Paper Tape Clipped Head Nails, Plastic Strip Nails	
Diameter	2.90 – 3.30 mm 0.113" – 0.131"	
Length	50 – 90 mm 2" – 3 1/2"	
SCRAIL®	SCRAIL® CHIPBOARD	SCRAIL® SPLITLESS
Inner & Outer diameter	2.9 / 3.5 mm 0.116" / 0.135" 3.1 / 3.9 mm 0.122" / 0.153"	2.8 / 3.2 mm 0.113" / 0.120" 2.9 / 3.3 mm 0.116" / 0.131"
Length	50 – 80 mm 2" – 3 1/4" 55 – 75 mm 2 1/4" – 3"	57 mm 2 1/4" 75 mm 3"



APPLICATIONS

- + Framing
- + Deck Construction
- + Sheathing
- + Crate and pallet construction
- + Flooring and subflooring

HANDLING

1. Insert nail strip into the back of the magazine
2. Slide the nail strip forward in the magazine
3. Pull the pusher back to engage the nail feeder to the nail strip
4. Slide the battery in the tool's handle until it is firmly seated
5. Press the power switch button to switch on the tool