







TRIMFAST® HEAVY DUTY MODEL 210TA

#### **DESCRIPTION**

- Engineered for the power and durability required for use with light gauge steel
- Accepts T-Nail style hardened trim pins
- Power to fasten to 14 ga steel at the speed of nailing to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Capable of driving pins 11/2" to 3" long
- Systems approach with tools and fasteners provides single source responsibility
- Comes standard with plastic carrying case
- No-Mar tip
- Depth of drive adjustment



## **CONTACT & SERVICE**

Our sales team is available at:

I +43 //24 2111-6/1 sales.int@beck-fastening.com www.beck-fastening.com

#### **PIN TYPE**

AST-100 TRIMFAST® HEAVY DUTY TRIM PINS



Raimund-Beck-Straße 1 | 5270 Mauerkirchen T +43 7724 2111-0 sales.int@beck-fastening.com www.beck-fastening.com









# TRIMFAST® HEAVY DUTY MODEL 210TA

#### TOOL CHARACTERISTICS

Height	Width	Length	Weight
11 1/2 inch	3 1/2 inch	12 inch	6.56 lbs
292 mm	89 mm	305 mm	3 kg

**Pressure** 85 - 120 psi | 6 - 8 bar

**Lubricant** Non-detergent pneumatic tool lubricant

**Recommended steel thickness** 

20 ga - 14 ga



Model 210TA

#### **FASTENER DATA**

Pin Type	AST-100-0150G	AST-100-0200G	AST-100-0250G	AST-100-0300G		
Wire	0.086"   2.20 mm					
Shank	Smooth					
Head	1/4"   6 mm					
Length	1 1/2"   39 mm	2"   50 mm	2 1/2"   63 mm	3"   75 mm		
Coating	Electro Galvanized					
Magazine Capacity	80 pins					

#### **ACTUATION & LOADING**

Actuation System: Sequential fire

Loading:

Magazine with latch

### **APPLICATIONS**

- James Hardie® XLD fiber cement trim to light gauge steel framing
- Miratec® treated exterior composite trim to light gauge steel framing
- Wood furring and exterior trim to light gauge steel framing
- Wood or metal furring to CMU