FASCO®
A BECK brand



F1A MB-25A

TOOL FEATURES

- Slim, round nose for precise nailing in tight corners
- Rubber comfort grip for non-slip handling and less fatigue
- Side window in the magazine helps prevent dry firing
- Quick Clear and reversible bumper for longer parts life

21 GAUGE MB BRADS

- Magazine with head channels for 12, 15, 18, 21, 25 and 30 mm
- Small 1.50 mm head for a clean, discreet finish
- Ideal for fine trim and decorative work

CONTACT & SERVICE

Our customer service is happy to assist you:

P +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The F1A MB-25A brad nailer is designed for precise fine fastening with 21 gauge MB brads in lengths from 12 to 30 mm. Its slim, round nose allows accurate nailing even in tight corners, while the rubber comfort grip reduces vibration and fatigue. Weighing only 870 g, with side loading, a 130-brad magazine and an operating pressure of 4 - 7 bar, it is ideal for mouldings and decorative trims, panels, doors and windows, glazing beads, stairs and parquet floors.

BECK

BECK Fastening GmbH
Raimund-Beck-Straße 1 | 5270 Mauerkirchen
T +43 7724 2111-0
sales@beck-fastening.com
www.beck-fastening.com

Follow us

F1A MB-25A

APPLICATIONS

- Mouldings & decorative trims
- Panels & profiled boards
- Doors, windows & glazing beads
- Stairs
- Boat interiors
- Parquet floors

HANDLING

1. Load MB brads from the side into the magazine
2. Connect air supply (4 - 7 bar)
3. Lubricate regularly with synthetic grease (PTFE) and keep the tool clean.

TOOL CHARACTERISTICS

Height	Width
165 mm	42 mm
6.50 inch	1.65 inch
Length	**Weight**
247 mm	0.87 kg
9.72 inch	1.92 lbs

Pressure
4 - 7 bar | 60 - 100 psi

Air consumption per shot
0.44 L. | 0.016 SCF
Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Shank (A x B)	0.70 x 0.90 mm 0.027 x 0.035"
Head (C)	1.50 mm	0.059"
Gauge	21
Length	12, 15, 18, 21, 25, 30 mm	1/2″, 19/32″, 11/16″, 53/64″, 63/64″, 1 3/16″
Magazine Capacity	130
Brad Type	MB BRADS

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)
$L_{WA,1s}$: 87.77 dB (A) - $K_{WA,1s}$, 2.5
$L_{pA,1s}$: 78.60 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)
is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Actuation

Loading: Side Loading



Changes and errors excepted. All rights reserved.
FASCO® is a registered trademark of the BECK Fastening GmbH.

VERSION
11/2026 EN