



F1B 14-16 STAPLER



TOOL FEATURES

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Bottom loading magazine speeds the reloading and keeps out the dirt

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application

FASCO[®] F1B 14-16 STAPLER:

- F1B 14-16
- F1B 14-16 AUT

DESCRIPTION

The F1B 14–16 series stapler line, together with the matching fasteners from BECK, is a compact, high-performance system designed for precise work with maximum efficiency. Thanks to its ergonomic design and robust construction, the staplers allow comfortable one-handed operation and easy maintenance. The trigger system (AUT version) offers maximum flexibility: a light press enables single-shot mode, while a full press switches to automatic firing. These staplers are ideal for demanding applications. The powerful staplers are designed to be especially precise and durable.

F1B 14-16 STAPLER

APPLICATION

- Decorations and coverings
- Automotive industry
- Furniture and beds
- Interior construction / Interior fittings
- Carpentry & joinery
- Textiles and footwear

HANDLING

1. Load staples into the magazine from below
2. Connect the air hose
3. Prevent dry and dirty tool operation by cleaning and lubricating regularly

FASTENER DATA

Staple Type	BECK 1400, BECK SP 3020, HAUBOLD 1400, PREBENA VF, BOSTITCH SP3020
Outside Crown	10,1 mm 0.4"
Inside Crown	8,7 mm 0.34"
Diameter	0,60 x 0,75 mm 0.023 x 0.029"
Length	6 - 16 mm ¼ - 5/8"
Capacity	180 (Standard, AUT)

ACTUATION & LOADING

ACTUATION SYSTEM:

F1B 14-16

Single actuation

F1B 14-16 AUT / AUT LM

Continual actuation

MAGAZINE:

Bottom loading

TOOL SPECIFICATION

TOOL	Height	Length	Width	Weight
F1B 14-16	157 mm 6.18 inch	218 mm 8.58 inch	42 mm 1.65 inch	0.78 kg 1.71 lbs
F1B 14-16 AUT	167 mm 6.57 inch	218 mm 8.58 inch	42 mm 1.65 inch	1.07 kg 2.36 lbs

Pressure

4 - 7 bar | 60 - 100 psi


5 - 7 bar | 70 - 100 psi (AUT Version)

Air consumption per shot

0.37 L. | 0.013 SCF performance at 90 psi | 6.2 bar (0.62 MPa)

0.17 L. | 0.006 SCF performance at 90 psi | 6.2 bar (0.62 MPa) (AUT Version)

VARIOUS VERSIONS AND COMBINATION OPTIONS



AUT - Automatic

Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of BECK Fastening GmbH.

SENCO®, BOSTITCH® and PREBENA® are all trademarks of their respective owner.

VERSION
02/2026 EN