



## F1B 14-16 STAPLERS



### TOOL FEATURES

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Bottom loading magazine speeds the reloading and keeps out the dirt

### FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application

### FASCO® F1B 14-16 STAPLER:

- F1B 14-16
- F1B 14-16 AUT

### DESCRIPTION

The F1B 14–16 series stapler line, together with the matching fasteners from BECK, is a compact, high-performance system designed for precise work with maximum efficiency. Thanks to its ergonomic design and robust construction, the staplers allow comfortable one-handed operation and easy maintenance. The trigger system (AUT version) offers maximum flexibility: a light press enables single-shot mode, while a full press switches to automatic firing. These staplers are ideal for demanding applications. The powerful staplers are designed to be especially precise and durable.

# F1B 14-16 STAPLERS

## APPLICATION

- Decorations and overings
- Automotive industry
- Furniture and beds
- Interior construction / Interior fittings
- Carpentry & joinery
- Textiles and footwear

## HANDLING

1. Load staples into the magazine from below
2. Connect the air hose
3. Prevent dry and dirty tool operation by cleaning and lubricating regularly

## FASTENER DATA

<b>Staple Type</b>	<b>BECK 1400, BECK SP 3020, HAUBOLD 1400, PREBENA VF, BOSTITCH SP3020</b>
<b>Outside Crown</b>	10.1 mm   0.4"
<b>Inside Crown</b>	8.7 mm   0.34"
<b>Diameter</b>	0.60 x 0.75 mm   0.023 x 0.029"
<b>Length</b>	6 - 16 mm   ¼ - ⅝"
<b>Capacity</b>	180 (Standard, AUT)

## ACTUATION & LOADING

### ACTUATION SYSTEM:

#### F1B 14-16

Single actuation

#### F1B 14-16 AUT / AUT LM

Continual actuation

### MAGAZINE:

Bottom loading

## TOOL SPECIFICATION

TOOL	Height	Length	Width	Weight
<b>F1B 14-16</b>	157 mm   6.18 inch	218 mm   8.58 inch	42 mm   1.65 inch	0.78 kg   1.71 lbs
<b>F1B 14-16 AUT</b>	167 mm   6.57 inch	218 mm   8.58 inch	42 mm   1.65 inch	1.07 kg   2.36 lbs

### Pressure

4 - 7 bar | 60 - 100 psi

5 - 7 bar | 70 - 100 psi (AUT Version)

### Air consumption per shot

0.37 L. | 0.013 SCF performance at 90 psi | 6.2 bar (0.62 MPa)

0.17 L. | 0.006 SCF performance at 90 psi | 6.2 bar (0.62 MPa) (AUT Version)

## VARIOUS VERSIONS AND COMBINATION OPTIONS



**AUT - Automatic**

Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of BECK Fastening GmbH.

HAUBOLD®, BOSTITCH® and PREBENA® are all trademarks of their respective owner.

**VERSION**  
**02/2026 US**