



**F1B 34DF-19**

### TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

### FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



### CONTACT & SERVICE

**Our customer service  
is happy to assist you:**

P +43 7724 2111-671  
[sales.int@beck-fastening.com](mailto:sales.int@beck-fastening.com)  
[www.beck-fastening.com](http://www.beck-fastening.com)

### DESCRIPTION

The F1B 34DF-19 stapling tool impresses with its robust construction and durable metal cap, making it ideally suited for professional continuous use. Its user-friendly operation and low-maintenance design ensure efficient and comfortable working. Thanks to its versatile range of applications, the tool is ideal for use in furniture and interior construction as well as in the automotive, textile, and footwear industries. The model is specifically designed for processing BECK 34 and BECK 74 staples and ensures reliable fastening results.

# F1B 34DF-19

## APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

## HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

| Height    | Width     |
|-----------|-----------|
| 157 mm    | 42 mm     |
| 6.18 inch | 1.65 inch |
| Length    | Weight    |
| 218 mm    | 0.88 kg   |
| 8.58 inch | 1.94 lbs  |

### Pressure

4 - 7 bar | 60 - 100 psi

### Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

|                   |                                                                            |
|-------------------|----------------------------------------------------------------------------|
| Outside Crown     | 4.50 mm   0.177"                                                           |
| Inside Crown      | 3.25 mm   0.128"                                                           |
| Diameter          | 0.50 x 0.75 mm<br>0.019 x 0.029"                                           |
| Length            | 6 - 19 mm  <br>1/4 - 3/4"                                                  |
| Magazine Capacity | 180                                                                        |
| Staple Type       | BECK 34, BECK 74,<br>DUOFAST 34,<br>HAUBOLD 1000, BEA<br>74,<br>PREBENA OB |

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 88.40 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 80.00 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit  
set by UNI EN ISO 12100-1/2

## ACTUATION & LOADING

Actuation System:  
Single Actuation

Loading: Bottom Loading

