



F1B 34DF-19

TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

The F1B 34DF-19 stapling tool impresses with its robust construction and durable metal cap, making it ideally suited for professional continuous use. Its user-friendly operation and low-maintenance design ensure efficient and comfortable working. Thanks to its versatile range of applications, the tool is ideal for use in furniture and interior construction as well as in the automotive, textile, and footwear industries. The model is specifically designed for processing BECK 34 and BECK 74 staples and ensures reliable fastening results.

BECK AMERICA

105 Industrial Park Drive
35661 Muscle Shoals, Alabama | USA
P +1 800 239 8665 | F +1 256 381 6659
sales.us@beck-fastening.com | www.beck-fastening.com

Follow us



F1B 34DF-19

APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	Weight
218 mm	0.88 kg
8.58 inch	1.94 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Outside Crown	4.50 mm 0.177"
Inside Crown	3.25 mm 0.128"
Diameter	0.50 x 0.75 mm 0.019 x 0.029"
Length	6 - 19 mm 1/4 - 3/4"
Magazine Capacity	180
Staple Type	BECK 34, BECK 74, DUOFAST 34, HAUBOLD 1000, BEA 74, PREBENA OB

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 88.40 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 80.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set
by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:

Single Actuation

Loading: Bottom Loading



Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the BECK Fastening GmbH.

BEA®, PREBENA®, HAUBOLD® and DUOFAST® are registered trademarks of their respective owners.

VERSION
05/2026 US