



FASCO® 4000 SERIES



TOOL FEATURES

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Bottom loading magazine speeds the reloading and keeps out the dirt

FASCO® FINE WIRE STAPLERS

- F1B 4000-19
- F21P 4000-25A



CONTACT & SERVICE

Our customer service is happy to assist you:

T +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The 4000 series from FASCO® stand for versatility, precision, and durability. They process the BECK 4000 staple as well as numerous models from other manufacturers with ease – always reliable and efficient. For particularly delicate tasks in textile and footwear manufacturing: the 4000 Series consistently delivers perfect results. The tools also demonstrate their strength and adaptability in the automotive industry. A dependable all-rounder that combines precise performance with maximum user comfort – for accurate, clean, and long-lasting results across every industry.

FASCO® 4000 SERIES

APPLICATIONS

- Trimming and Paneling
- Furniture and Beds
- Interior Construction
- Textiles and Footwear

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

FASTENER DATA

	F1B 4000-19	F21P 4000-25A
Outside Crown	4,90 mm 0.192"	
Inside Crown	3,25 mm 0.127"	
Diameter	0,70 x 0,90 mm 0.027" x 0.035"	
Length	6 - 19 mm ¼ - ¾"	12 - 25 mm 1/2 - 1"
Magazine Capacity	140	
Staple Type	BECK 4000	
Similar to	ATRO 40, ATRO 93, HAUBOLD 4000, PREBENA TB	

TOOL CHARACTERISTICS

	F1B 4000-19	F21P 4000-25A
Height	157 mm 6.18 inch	182 mm 7.16 inch
Length	218 mm 8.58 inch	226 mm 8.90 inch
Width	42 mm 1.65 inch	49 mm 1.93 inch
Weight	0,95 kg 2.08 lbs	1,05 kg 2.32 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

ACTUATION & LOADING

ACTUATION SYSTEM:

Single actuation (F1B 4000-19)

Contact actuation (F21P 4000-25A)

LOADING:

Bottom loading



Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the BECK Fastening GmbH.

ATRO®, PREBENA® and HAUBOLD® are all trademarks of their respective owner.

VERSION
02/2026 EN