



TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

Maximum reliability for everyday workshop use: the F1B 54DF-19 stands out thanks to its extremely durable housing and solid metal cap. This tool has been designed to withstand tough industrial conditions. Thanks to its straightforward maintenance and intuitive operation, workflow remains consistently high. The tool is a true all-rounder and performs superbly in upholstered furniture manufacturing, vehicle construction, and leather and textile processing. As a specialist for BECK 54 staples, this model guarantees precision placement with every fastening.

BECK AMERICA

105 Industrial Park Drive
35661 Muscle Shoals, Alabama | USA
P +1 800 239 8665 | F +1 256 381 6659
sales.us@beck-fastening.com | www.beck-fastening.com

Follow us



F1B 54DF-19

APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	Weight
218 mm	0,94 kg
8.58 inch	2.06 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Outside Crown	4.50 mm 0.177"
Inside Crown	3.25 mm 0.128"
Diameter	0.50 x 1.25 mm 0.019 x 0.049"
Length	6 - 19 mm 1/4 - 3/4"
Magazine Capacity	110
Staple Type	BECK 54, DUOFAST 54, PREBENA TF

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 89.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 79.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit
set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:

Single Actuation

Loading: Bottom Loading

