



## F1B 64-16 STAPLERS



### TOOL FEATURES

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Bottom loading magazine speeds the reloading and keeps out the dirt

### FASCO® FINE WIRE STAPLERS

- F1B 64-16
- F1B 64-16 AUT



### CONTACT & SERVICE

Our customer service is happy to assist you:

T +43 7724 2111-671  
sales.int@beck-fastening.com  
www.beck-fastening.com

### DESCRIPTION

The F1B 64-16 and 64-16 AUT combine ergonomic design, lightweight handling, and outstanding durability. They process the BECK 1800 staple and numerous models from other manufacturers with ease and precision. Their versatility makes them true all-rounders: whether in the automotive industry, furniture and interior construction, or textile and panel applications – they always deliver perfect results. The ideal choice for anyone who values efficiency, comfort, and maximum reliability.

# F1B 64-16 STAPLERS

## APPLICATIONS

- Upholstery
- Interior Construction
- Trimming and Paneling
- Carpentry & Joinery
- Automotive Industry
- Textiles and Footwear
- Furniture and Beds

## HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## FASTENER DATA

<b>Outside Crown</b>	12,45 mm   0.49"
<b>Inside Crown</b>	11,25 mm   0.44"
<b>Diameter</b>	0,50 x 0,75 mm   0.019 x 0.029"
<b>Length</b>	6 - 16 mm   ¼ - ⅝"
<b>Magazine Capacity</b>	180
<b>Staple Type</b>	BECK 1800
<b>Similar to</b>	BEA 64, DUOFAST 30, HAUBOLD 1800

## TOOL CHARACTERISTICS

	F1B 64-16	F1B 64-16 AUT
<b>Height</b>	157 mm 6.18 inch	167 mm 6.57 inch
<b>Length</b>	218 mm 8.58 inch	218 mm 8.58 inch
<b>Width</b>	42 mm 1.65 inch	42 mm 1.65 inch
<b>Weight</b>	0,88 kg 1.94 lbs	1,12 kg 2.47 lbs

### Pressure

4 - 7 bar | 60 - 100 psi (F1B 64-16) /  
5 - 7 bar | 70 - 100 psi (F1B 64-16 AUT)

### Air consumption per shot

0.37 L. | 0.013 SCF (F1B 64-16)  
0.17 L. | 0.006 SCF (F1B 64-16 AUT)  
Performance at 90 psi | 6.2 bar (0.62 MPa)

## ACTUATION & LOADING

### ACTUATION SYSTEM:

Single actuation (F1B 64-16)

Continual actuation (F1B 64-16 AUT)

### LOADING:

Bottom loading

