



F1B 84-16 STAPLERS



TOOL FEATURES

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Bottom loading magazine speeds the reloading and keeps out the dirt

FASCO® STAPLERS

- F1B 84-16
- F1B 84-16 AUT



CONTACT & SERVICE

Our customer service is happy to assist you:

T +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The F1B 84-16 and 84-16 AUT tools impress with their ergonomic design, lightweight construction, and exceptional durability. They process BECK 84 staples, BECK SBNK 4023, as well as numerous models from other manufacturers with ease. Thanks to their versatility, these tools are ideally suited for a wide range of applications – from the automotive industry to interior paneling and furniture manufacturing, all the way to textile processing and coverings. Perfect for precise and efficient work in every industry.

F1B 84-16 STAPLERS

APPLICATIONS

- Upholstery
- Trimming and Paneling
- Automotive Industry
- Furniture and Beds
- Interior Construction
- Carpentry & Joinery
- Textiles and Footwear

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

FASTENER DATA

Outside Crown	12,3 mm 0.48"
Inside Crown	10,90 mm 0.43"
Diameter	0,55 x 1,00 mm 0.022 x 0.039"
Length	6 - 16 mm ¼ - 5/8"
Magazine Capacity	130
Staple Type	BECK SBNK 4023, BECK 84, BOSTITCH SBNK4023, TYPE 84, ATRO 84, PREBENA AD

TOOL CHARACTERISTICS

	F1B 84-16	F1B 84-16 AUT
Height	157 mm 6.18 inch	167 mm 6.57 inch
Length	218 mm 8.58 inch	218 mm 8.58 inch
Width	42 mm 1.65 inch	42 mm 1.65 inch
Weight	0,78 kg 1.71 lbs	1,12 kg 2.47 lbs

Pressure:

4 - 7 bar | 60 - 100 psi (F1B 84-16) /
5 - 7 bar | 70 - 100 psi (F1B 84-16 AUT)

Air consumption per shot

0.37 L. | 0.013 SCF (F1B 84-16)
0.17 L. | 0.006 SCF (F1B 84-16 AUT)
Performance at 90 psi | 6.2 bar (0.62 MPa)

ACTUATION & LOADING

ACTUATION SYSTEM:

Single actuation (F1B 84-16)
Continual actuation (F1B 84-16 AUT)

LOADING:

Bottom loading

