FASCO®
A BECK brand

F1B A11-16 STAPLERS

TOOL FEATURES

- Industrial stapler available with single-shot and continual actuation options
- Fewer interruptions thanks to extended magazine capacity
- Balanced ergonomics for fatigue-free operation even at a maximum speed of 1,600 cycles per minute

FINE WIRE STAPLES

- Can be used with a wide variety of materials and surfaces
- Offer tip geometry tailored to the specific application
- Available in a wide range of materials

FASCO® F1B A11-16 STAPLERS

- F1B A11-16
- F1B A11-16 LM
- F1B A11-16 AUT LM

DESCRIPTION

Compact, powerful, smart – our devices impress with robust design, high serviceability, and ergonomic one-handed operation. The innovative single-trigger system (AUT) with quick-release valve provides full control: A light press delivers a single shot, while fully pressing the trigger activates continuous firing – for efficient work without mode switching. The firing speed is adjusted via a dial near the trigger to set once before use. After that, operation is entirely one-handed. A smart system for maximum productivity.

BECK

RAIMUND BECK KG - Wire Staples Company
Raimund-Beck-Straße 1 | 5270 Mauerkirchen
+43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

Follow us

F1B A11-16 STAPLERS

APPLICATIONS

- Insulation
- Roofing
- Prefabricated house construction
- Interior finishing

HANDLING

1. Load staples into the magazine from below
2. Connect the air hose
3. Prevent dry and dirty tool operation by cleaning and lubricating regularly

ACTUATION & LOADING

ACTUATION SYSTEM:

F1B A11-16 / LM:
Single actuation

F1B A11-16 AUT LM:
Continual actuation

LOADING:
Bottom loading

FASTENER DATA

Outside Crown	10,80 mm | 0.425"
Inside Crown	9,50 mm | 0.374"
Diameter	0,53 x 1,25 mm | 0.021 x 0.049"
Length	6 - 16 mm | ¼ -5/8"
Magazine Capacity	110 (Standard) 230 (LM)
Staple Type	BECK 11, ARROW T50, HAUBOLD 1100, KIHLBERG JK671, RAPID 11, RAPID 132, RAPID 140, RAPID A11, PREBENA MW, PREBENA PF, SENCO H

TOOL CHARACTERISTICS

TOOL	Height	Length	Width	Weight
F1B A11-16	157 mm 6.18 inch	218 mm 8.58 inch	42 mm 1.65 inch	780 g 1.71 lbs
F1B A11-16 LM	157 mm 6.18 inch	376 mm 14.80 inch	42 mm 1.65 inch	990 g 2.18 lbs
F1B A11-16 AUT LM	167 mm 6.57 inch	376 mm 14.80 inch	42 mm 1.65 inch	1370 g 3.00 lbs

Pressure
4 - 7 bar | 60 - 100 psi / 4,5 - 7 bar | 65 - 100 psi /
5 - 7 bar | 70 - 100 psi (AUT variations)

Air consumption per sho
0.37 L. | 0.013 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)
0.17 L. | 0.006 SCF Performance at 90 psi | 6.2 bar (0.62 MPa) (AUT variations)

VARIOUS DESIGNS AND COMBINATION OPTIONS

LM - Long Magazine

AUT - Automatic

Changes and errors excepted. All rights reserved.
FASCO® is a registered trademark of the BECK Fastening GmbH. ARROW®, HAUBOLD®, KIHLBERG®, RAPID®, PREBENA® and SENCO® are all trademarks of their respective owner.

VERSION
02/2026 EN