FASCO®
A BECK brand

F1B N30-19

TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application

CONTACT & SERVICE

Our customer service is happy to assist you:

P +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The F1B N30-19 stapler impresses with its robust construction, featuring a new metal cap, whilst also offering particularly easy handling and a maintenance-friendly design. Thanks to its long nose, it is ideal for precise work, even in hard-to-reach places. It is versatile – from furniture and interior design to the automotive, textile and footwear industries – and perfectly suited for use with BECK PN30 staples.

BECK

BECK Fastening GmbH
Raimund-Beck-Straße 1 | 5270 Mauerkirchen
T +43 7724 2111-0
sales@beck-fastening.com
www.beck-fastening.com

Follow us

F1B N30-19

APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	**Weight**
218 mm	0.94 kg
8.58 inch	2.07 lbs

Pressure
4 - 7 bar | 60 - 100 psi

Air consumption per shot
0.37 L. | 0.013 SCF
Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	5.20 mm	0.205"
Inside Crown	3.90 mm	0.153"
Diameter	0.60 x 0.75 mm 0.023 x 0.029“
Length	6 - 19 mm | 1/4 - 3/4"
Magazine Capacity	180
Staple Type	BECK PN 30, PASLODE PN30, PREBENA EO

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)
$L_{WA,1s}$: 88.40 dB (A) - $K_{WA,1s}$, 2.5
$L_{pA,1s}$: 80.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)
is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Actuation

Loading: Bottom Loading

Changes and errors excepted. All rights reserved.
FASCO® is a registered trademark of the BECK Fastening GmbH.
PASLODE® and PREBENA® are all trademarks of their respective owner.

VERSION
05/2026 EN