



F1B N50-19

TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

**Our customer service
is happy to assist you:**

P +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The F1B N50-19 stapler impresses with its robust design featuring a new metal cap, while also offering particularly easy handling and a maintenance-friendly construction. Thanks to its long nose, it is ideal for precise work even in hard-to-reach areas. It is highly versatile – from furniture and interior construction to the automotive, textile, and footwear industries – and perfectly suited for processing BECK PN50 staples.

F1B N50-19

APPLICATION

- Finish & trim
- Automotive
- Furniture & bedding
- Millwork
- Textile & Shoes

HANDLING

1. Insert staples into the magazine from underneath.
2. Connect the compressed air hose.
3. Prevent dry or dirty tools by regularly lubricating and cleaning them.

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	Weight
218 mm	0.95 kg
8.58 inch	2.10 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	5.20 mm 0.205"
Inside Crown	3.90 mm 0.153"
Diameter	0.60 x 1.20 mm 0.023 x 0.047"
Length	6 - 19 mm 1/4 - 3/4"
Capacity	110
Staple Type	BECK PN 50, BEA 99, PASLODE PN50, PREBENA EN

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 88.40 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 80.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

Below the declaration limit UNI
EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Shot

Loading: Bottom loading

