



**F1B N50-19**

### TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

### FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



### CONTACT & SERVICE

Our sales team  
is happy to assist you:

P +1 800 239 8665  
[sales@beck-america.com](mailto:sales@beck-america.com)  
[www.beck-america.com](http://www.beck-america.com)

### DESCRIPTION

The F1B N50-19 stapler impresses with its robust design featuring a new metal cap, while also offering particularly easy handling and a maintenance-friendly construction. Thanks to its long nose, it is ideal for precise work even in hard-to-reach areas. It is highly versatile – from furniture and interior construction to the automotive, textile, and footwear industries – and perfectly suited for processing BECK PN50 staples.

# F1B N50-19

## APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

## HANDLING

1. Insert staples into the magazine from underneath.
2. Connect the compressed air hose.
3. Prevent dry or dirty tools by regularly lubricating and cleaning them.

## TOOL CHARACTERISTICS

| Height    | Width     |
|-----------|-----------|
| 157 mm    | 42 mm     |
| 6.18 inch | 1.65 inch |
| Length    | Weight    |
| 218 mm    | 0.95 kg   |
| 8.58 inch | 2.10 lbs  |

### Pressure

4 - 7 bar | 60 - 100 psi

### Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

## FASTENER DATA

|               |                                                    |
|---------------|----------------------------------------------------|
| Outside Crown | 5.20 mm   0.205"                                   |
| Inside Crown  | 3.90 mm   0.153"                                   |
| Diameter      | 0.60 x 1.20 mm<br>0.023 x 0.047"                   |
| Length        | 6 - 19 mm  <br>1/4 - 3/4"                          |
| Capacity      | 110                                                |
| Staple Type   | BECK PN 50,<br>BEA 99, PASLODE<br>PN50, PREBENA EN |

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 88.40 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 80.00 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

Below the declaration limit UNI  
EN ISO 12100-1/2

## ACTUATION & LOADING

Actuation System:

Single Shot

Loading: Bottom loading

