



TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

The F1B S30-19 stapler impresses with its robust construction and newly developed metal cover, ensuring high durability for everyday use. Thanks to its user-friendly operation and low-maintenance design, the tool can be used particularly efficiently. The extended nose allows for precise work even in hard-to-reach areas. Whether in furniture manufacturing, interior construction, or the automotive, textile, and footwear industries – the tool is highly versatile and specifically designed for processing BECK PS30 staples.

F1B N30-19

APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

HANDLING

1. Insert staples into the magazine from underneath.
2. Connect the compressed air hose.
3. Prevent dry or dirty tools by regularly lubricating and cleaning them.

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	Weight
218 mm	0.95 kg
8.58 inch	2.09 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	8.60 mm 0.338"
Inside Crown	7.10 mm 0.279"
Diameter	0.60 x 0.80 mm 0.024 x 0.031"
Length	6 - 16 mm 1/4 - 5/8"
Capacity	160
Staple Type	BECK PS 30, PASLODE PS30, PREBENA HO

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 89.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 79.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

Below the declaration limit UNI
EN ISO 12100-1/2

