



**F1B SJK-19**

### TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

### FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



### CONTACT & SERVICE

**Our customer service  
is happy to assist you:**

P +43 7724 2111-671  
[sales.int@beck-fastening.com](mailto:sales.int@beck-fastening.com)  
[www.beck-fastening.com](http://www.beck-fastening.com)

### DESCRIPTION

The F1B SJK-19 stapler was developed for precise and reliable fastening applications and impresses with its robust and low-maintenance design. Its ergonomic handling enables comfortable operation, even during extended periods of use. Thanks to its slim design, the tool is ideal for applications in hard-to-reach areas. It processes BECK SJK staples with lengths of up to 19 mm and can be used in a wide range of applications, including furniture manufacturing, interior construction, as well as the textile and automotive industries.

# F1B SJK-19

## APPLICATION

- Finish & trim
- Automotive
- Furniture & bedding
- Millwork
- Textile & Shoes

## HANDLING

1. Insert staples into the magazine from underneath.
2. Connect the compressed air hose.
3. Prevent dry or dirty tools by regularly lubricating and cleaning them.

## TOOL CHARACTERISTICS

| Height    | Width     |
|-----------|-----------|
| 157 mm    | 42 mm     |
| 6.18 inch | 1.65 inch |
| Length    | Weight    |
| 218 mm    | 0.93 kg   |
| 8.58 inch | 2.05 lbs  |

### Pressure

4 - 7 bar | 60 - 100 psi

### Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

## FASTENER TYPE

|               |                                  |
|---------------|----------------------------------|
| Outside Crown | 4.25 mm   0.167"                 |
| Inside Crown  | 2.60 mm   0.102"                 |
| Diameter      | 0.60 x 0.70 mm<br>0.024 x 0.028" |
| Length        | 6 - 19 mm  <br>1/4 - 3/4"        |
| Capacity      | 180                              |
| Staple Type   | BECK SJK,<br>ATRO SJK            |

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 89.02 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 79.70 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

Below the declaration limit UNI  
EN ISO 12100-1/2

## ACTUATION & LOADING

ACTUATION SYSTEM:

Single Shot

Loading: Bottom loading

