



F1B SJK-19

TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

The F1B SJK-19 stapler was developed for precise and reliable fastening applications and impresses with its robust and low-maintenance design. Its ergonomic handling enables comfortable operation, even during extended periods of use. Thanks to its slim design, the tool is ideal for applications in hard-to-reach areas. It processes BECK SJK staples with lengths of up to 19 mm and can be used in a wide range of applications, including furniture manufacturing, interior construction, as well as the textile and automotive industries.

BECK AMERICA

105 Industrial Park Drive
35661 Muscle Shoals, Alabama | USA
P +1 800 239 8665 | F +1 256 381 6659
sales.us@beck-fastening.com | www.beck-fastening.com

Follow us



F1B SJK-19

APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

HANDLING

1. Insert staples into the magazine from underneath.
2. Connect the compressed air hose.
3. Prevent dry or dirty tools by regularly lubricating and cleaning them.

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	Weight
218 mm	0.93 kg
8.58 inch	2.05 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	4.25 mm 0.167"
Inside Crown	2.60 mm 0.102"
Diameter	0.60 x 0.70 mm 0.024 x 0.028"
Length	6 - 19 mm 1/4 - 3/4"
Capacity	180
Staple Type	BECK SJK, ATRO SJK

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 89.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 79.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

Below the declaration limit UNI
EN ISO 12100-1/2

ACTUATION & LOADING

ACTUATION SYSTEM:

Single Actuation

Loading: Bottom loading

