



F1B SR3-16 STAPLER



TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a firm hold
- One-handed magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to particularly durable composite magazine

FINE WIRE STAPLES

- Can be used on a wide variety of materials and surfaces
- Have a tip geometry adapted to the application
- Are available in a wide variety of materials

FASCO® F1B SR3-16 STAPLER:

- F1B SR3-16
- F1B SR3-16 AUT
- F1B SR3-16 AUT LM

DESCRIPTION

The staplers in the F1B SR3-16 series are powerful pneumatic tools for fast and precise stapling of materials such as wood, textiles, or packaging. They are available in various designs, including automatic models for high cycle rates and versions with long magazines for longer working intervals without reloading. The ergonomic design and reliable technology ensure efficient and comfortable use in trade and industry.

F1B SR3-16 STAPLER

APPLICATION

- Decoration and paneling
- Automotive industry
- Furniture and beds
- Interior design
- Carpenters and joiners
- Textiles and shoes

HANDLING

1. Load staples into the magazine from below
2. Connect the air hose
3. Prevent dry and dirty tool operation by cleaning and lubricating regularly

FASTENER DATA

Outside Crown	12,8 mm 0.5"
Inside Crown	11,6 mm 0.46"
Diameter	0,50 x 0,75 mm 0.020 x 0.030"
Length	6 - 16 mm ¼ - 5/8"
Capacity	180 (Standard, AUT) 390 (LM)
Stapler Type	BECK 3, BOSTITCH SB3020, PREBENA PM, SENCO B (=3)

TOOL CHARACTERISTICS

TOOL	Height	Length	Width	Weight
F1B SR3-16	157 mm 6.18 inch	218 mm 8.58 inch	42 mm 1.65 inch	0.88 kg 1.94 lbs
F1B SR3-16 AUT	167 mm 6.57 inch	218 mm 8.58 inch	42 mm 1.65 inch	1.12 kg 2.47 lbs
F1B SR3-16 AUT LM	167 mm 6.57 inch	376 mm 14.80 inch	42 mm 1.65 inch	1.37 kg 3 lbs

Pressure

4 - 7 bar | 60 - 100 psi / 4,5 - 7 bar | 65 - 100 psi
5 - 7 bar | 70 - 100 psi (AUT Version)

Air consumption per shot

0.37 L. | 0.013 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)
0.17 L. | 0.006 SCF Performance at 90 psi | 6.2 bar (0.62 MPa) (AUT Version)

ACTUATION & LOADING

ACTUATION SYSTEM:

F1B SR3-16

Single Actuation

F1B SR-16 AUT / AUT LM

Continual Actuation

MAGAZINE:

Bottom loading

VERSCHIEDENE AUSFÜHRUNGEN UND KOMBINATIONSMÖGLICHKEITEN WIE



Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the BECK Fastening GmbH.

SENCO®, BOSTITCH® and PREBENA® are all trademarks of their respective owner.

VERSION
02/2026 US