



F1B SR5-16 STAPLER



TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a firm hold
- One-handed magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to particularly durable composite magazine

FINE WIRE STAPLES

- Can be used on a wide variety of materials and surfaces
- Have a tip geometry adapted to the application
- Are available in a wide variety of materials

FASCO® F1B SR5-16 STAPLER:

- F1B SR5-16
- F1B SR5-16 AUT
- F1B SR5-16 AUT LM
- F1B SR5-16 LN50
- F1B SR5-16 LMTL RC MC S/PUSH

DESCRIPTION

The F1B SR5-16 series offers powerful pneumatic staplers for precise fastening. Models with a long nose allow access to hard-to-reach areas, while variants with a long magazine require less frequent reloading. Automatic versions ensure a particularly high firing rate. Thanks to their ergonomic design and robust construction, they are ideal for trade and industry. The F1B SR5-16 LMTL RC MC S/PUSH device was specially developed for automation. It is equipped with a top-loading, double-length magazine with a control valve.

F1B SR5-16 STAPLER

APPLICATION

- Decoration and paneling
- Automotive industry
- Furniture and beds
- Interior design
- Carpenters and joiners
- Textiles and shoes

HANDLING

1. Load staples into the magazine from below
2. Connect the air hose
3. Prevent dry and dirty tool operation by cleaning and lubricating regularly

FASTENER DATA

Outsid Crown	12,8 mm 0.5"
Inside Crown	11,6 mm 0.46"
Diameter	0,50 x 1,25 mm 0.020 x 0.050"
Length	6 - 16 mm ¼ - ⅝"
Capacity	110 (Standard, AUT) 230 (LM)
Staple Type	BECK 5, BOSTITCH SB5019, PREBENA P, SENCO F (=5)

TOOL CHARACTERISTICS

TOOL	Height	Length	Width	Weight
F1B SR5-16	157 mm 6.18 inch	218 mm 8.58 inch	42 mm 1.65 inch	0,87 kg 1.92 lbs
F1B SR5-16 AUT	167 mm 6.57 inch	218 mm 8.58 inch	42 mm 1.65 inch	1,12 kg 2.47 lbs
F1B SR5-16 AUT LM	167 mm 6.57 inch	376 mm 14.80 inch	42 mm 1.65 inch	1,37 kg 3 lbs
F1B SR5-16 LN50	205 mm 8.07 inch	218 mm 8.58 inch	42 mm 1.65 inch	0,84 kg 1.89 lbs
F1B SR5-16 LMTL RC MC S/PUSH	192 mm 7.56 inch	376 mm 14.80 inch	57 mm 2.25 inch	1,31 kg 2.88 lbs

Pressure

4 - 7 bar | 60 - 100 psi / 4,5 - 7 bar | 65 - 100 psi / 5 - 7 bar | 70 - 100 psi (LN, AUT Version)

Air consumption per shot

0.37 L. | 0.013 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)
0.17 L. | 0.006 SCF Performance at 90 psi | 6.2 bar (0.62 MPa) (AUT Version)

ACTUATION & LOADING

ACTUATION SYSTEM:

F1B SR5-16 / LN50

Single actuation

F1B SR5-16 AUT / AUT LM

Continual actuation

F1B SR5-16 LMTL RC MC S/PUSH

Remote actuation

MAGAZINE TYPE:

Bottom loading

Top loading (LMTL)

VARIOUS DESIGNS AND COMBINATION OPTIONS SUCH AS



LMTL - extra long magazine



LN - long nose



LM - long magazine



AUT - automatic

Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the BECK Fastening GmbH.

SENCO®, BOSTITCH® and PREBENA® are all trademarks of their respective owner.

VERSION
02/2026 US