



F1B W50-16

TOOL FEATURES

- Comfort grip reduces vibration transmission and provides a secure hold
- One-hand magazine lock for quick reloading
- Reversible buffer with significantly longer service life
- Easy maintenance thanks to an especially durable composite magazine

FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

The F1B W50-16 is the top choice for maximum precision in demanding working conditions. Thanks to its extended nose, this stapler effortlessly handles even awkward angles and hard-to-reach areas in furniture making or interior fit-out. Its robust design is specifically engineered for continuous industrial use. Yet, thanks to its low-maintenance and ergonomic construction, the tool remains comfortable to use at all times. Whether in textile manufacturing or the automotive sector – the tool impresses with its versatility. It is precisely calibrated for use with BECK PW50 staples, guaranteeing an absolutely reliable and strong bond every time.

F1B W50-16

APPLICATIONS

- Finish & Trim
- Automotive
- Furniture & Bedding
- Millwork
- Textile & Shoes

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
157 mm	42 mm
6.18 inch	1.65 inch
Length	Weight
218 mm	0.78 kg
8.58 inch	1.71 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	13 mm 0.512"
Inside Crown	11.60 mm 0.456"
Diameter	0.60 x 1.20 mm 0.023 x 0.047"
Length	6 - 16 mm 1/4 - 5/8"
Magazine Capacity	110
Staple Type	BECK PW 50, PASLODE P W50, PREBENA PA

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.12 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 81.30 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit
set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Actuation

Loading: Bottom Loading

