




F21P 65DF-25A



TOOL FEATURES

- Contact actuation
- One-handed release for quick reloading
- Comfortable rubber grip

MEDIUM WIRE STAPLES

- For medium crown staples
- Up to 25 mm (0.984") leg length
- With different point options available
- Are available in different materials



CONTACT & SERVICE

Our sales team
is available at:

P +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

The F21P 65DF-25A medium wire stapler offers the ideal combination of lightweight construction, balanced handling and comfortable operation. Thanks to the slim nose, precise fastening with a clear view of the work area is possible at all times. Together with the BECK 65 staples, the tool is ideal for decorative trims and panelling, as well as for use in furniture and bed production and in joinery and carpentry workshops.

F21P 65DF-25A

APPLICATIONS

- Finish & Trim
- Furniture & Bedding
- Millwork

HANDLING

1. Load staples from the top into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
182 mm	49 mm
7.16 inch	1.93 inch
Length	Weight
228 mm	1,02 kg
8.98 inch	2.25 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot

0.37 L. | 0.013 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Outside Crown	12.50 mm 0.492"
Inside Crown	10.80 mm 0.425"
Diameter	0.75 x 1.25 mm 0.029 x 0.049"
Length	12 - 25 mm 1/2 - 1"
Magazine Capacity	110
Staple Type	BECK 65, DUOFAST 65, HAUBOLD 9000, PREBENA M

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 97.20 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 90.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit
set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Actuation

Loading: Bottom Loading



Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the RAIMUND BECK KG.

PREBENA®, DUOFAST® and HAUBOLD® are all trademarks of their respective owner.

VERSION
05/2026 EN