



F21T GN-40A GS



TOOL FEATURES

- Light weight and easy to handle
- Forked-type safety specially designed for glazing strips
- Rubber comfort grip ensures non-slip handling

PINS AND BRADS

- GN brads (18 GA)
- Universally applicable, e.g. for windows and doors or even furniture construction.



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

Specially designed for fixing glazing strips. The tool automatically bends the brads away from the glass, to avoid breakages. Adjustable guides and rollers allow to put the tool in the desired position. A patented quick clear system for unjamming.

F21T GN-40A GS

APPLICATIONS

- Glazing

HANDLING

1. Load brads from the side into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively, cleaning regularly

TOOL CHARACTERISTICS

Height	Width
222 mm	68 mm
8.74 inch	2.68 inch
Length	Weight
285 mm	1,28 kg
11.22 inch	2.82 lbs

Pressure

5 - 7 bar | 70 - 100 psi

Air consumption per shot

0.43 L. | 0.015 SCF

Leistung bei 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA BRADS

Shank	0.039 x 0.050 mm 1.0 x 1.27"
Head	2.20 mm 0.086"
Length	15 – 40 mm 5/8" – 1 9/16"
Capacity	105 brads
Typ	GN (18 GAUGE)

NOISE CHARACTERISTICS

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 98.70 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 91.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit
set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation:

Single sequential actuation

Loading: Side loading

