



F21T SG-25A
F21T SG-25A ST



TOOL FEATURES

- Contact actuation and single-shot actuation (ST version)
One-handed latch for quick reloading
Ergonomic rubber comfort grip

MEDIUM WIRE STAPLES

- For medium crown staples
- Up to 40 mm (1 9/16") leg length
- With different point options available
- Are available in different materials



CONTACT & SERVICE

Our sales team
is happy to assist you:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

The F21T SG-25A is a versatile medium-wire stapler designed for precision applications in furniture manufacturing and interior fit-out. Its long, narrow nose provides excellent visibility of the work area, enabling accurate staple placement even in hard-to-reach locations. The practical one-handed latch allows for fast reloading, ensuring efficient operation and reduced downtime. The tool is compatible with a variety of staple types, including BECK G 4450 and BECK 782 staples.

BECK AMERICA

105 Industrial Park Drive
35661 Muscle Shoals, Alabama | USA
P +1 800 239 8665 | F +1 256 381 6659
sales.us@beck-fastening.com | www.beck-fastening.com

Follow us



F21T SG-25A & F21T SG-25A ST

APPLICATION

- Finish & trim
- Furniture & bedding
- Millwork

HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
216 mm	49 mm
8.50 inch	1.93 inch
Length	Weight
228 mm	1,08 kg
8.98 inch	2.37 lbs

Pressure

4 - 7 bar | 60 - 100 psi

Air consumption per shot Schuss

0.43 L. | 0.015 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Outside Crown	10.10 mm 0.397"
Inside Crown	7.80 mm 0.307"
Diameter	1.00 x 1.25 mm 0.039 x 0.049"
Length	12 - 25 mm 1/2 - 1"
Magazine Capacity	110
Staple Type	BECK G 4450, BECK 782, PREBENA G, SENCO G4450, SENCO M, KIHLEBERG JK782

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 97.20 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 90.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System::

Contact actuation

Single-shot actuation (ST)

Magazine: Bottom loading



Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the BECK Fastening GmbH. ATRO®, DUOFAST®, HAUBOLD®, PREBENA®, SENCO® and KIHLEBERG® are all trademarks of their respective owner.

VERSION
05/2026 US