



**F23A A64-35PB**  
**F23A A64-50PB**



### TOOL FEATURES

- Light weight and powerful tools
- Lock-out, to prevent dry firing
- Removable no-mar tip and extra rubber tip stored

### PINS AND BRADS

- For A64 pins and micro brads with 0.57 mm wire diameter (23 Gauge)
- Up to 35 mm (F23 A64-35PB) or 50 mm length (F23A A64-50PB)
- Galvanized



### CONTACT & SERVICE

**Our sales team  
is available at:**

P +43 7724 2111-671  
sales@beck-fastening.com  
www.beck-fastening.com

### DESCRIPTION

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- No-mar tip avoids marking of soft wood
- Slim nose ensures good visibility and precision

# F23A A64-35PB // F23A A64-50PB

## APPLICATIONS

- Garden furniture
- Upholstering
- Drawer guides
- Case backs
- Kitchen units
- Mouldings and decorative trims
- Sheathing
- Baseboards
- Doors and windows
- Boat interiors
- Shoe making
- Glazing and beading
- Manufactured houses

## HANDLING

1. Load pins or brads from the side into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS F23A A64-35PB

Height	Width
200 mm	62 mm
7.87 inch	2.44 inch
Length	Weight
220 mm	1.15 kg
8.66 inch	2.53 lbs

### Pressure

5 - 7 bar | 70 - 100 psi

### Air consumption per shot

0.44 L. | 0.016 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA F23A A64-35PB

<b>Diameter</b>	0.64 x 0.64 mm   0.025 x 0.025"
<b>Brads Head</b>	0.87 mm   0.034"
<b>Length</b>	12   15   20   22   25   28   30   32   35 1/2   5/8   3/4   7/8   1   1 1/8   1 3/16   1 1/4   1 3/8
<b>Magazine Capacity</b>	120 pins / brads
<b>Fastener Type</b>	A64 PINS & Micro Brads (23 GAUGE)

## F23A A64-35PB

### NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 83.00 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 70.00 dB (A) -  $K_{pA,1s}$  , 2.5

### VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit  
set by UNI EN ISO 12100-1/2

### ACTUATION & LOADING

Actuation System: Single Shot

Loading: Side Loading

## TOOL CHARACTERISTICS F23A A64-50PB

Height	Width
228 mm	62 mm
8.98 inch	2.44 inch
Length	Weight
225 mm	1.23 kg
8.86 inch	2.70 lbs

### Pressure

5 - 7 bar | 70 - 100 psi

### Air consumption per shot

0.50 L. | 0.018 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA A23A A64-50PB

<b>Diameter</b>	0.64 x 0.64 mm   0.025 x 0.025"
<b>Brads Head</b>	0.87 mm   0.034"
<b>Length</b>	12   15   20   22   25   28   30   32   35   38   40   45   50 mm 1/2   5/8   3/4   7/8   1   1 1/8   1 3/16   1 1/4   1 3/8   1 1/2   1 9/16   1 3/4   2"
<b>Capacity</b>	120 brads / pins
<b>Fastener Type</b>	A64 PINS & Micro Brads (23 GAUGE)

## F23A A64-50PB

### NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 87.00 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 74.00 dB (A) -  $K_{pA,1s}$  , 2.5

### VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit  
set by UNI EN ISO 12100-1/2

### ACTUATION & LOADING

Actuation System: Single Shot

Loading: Side Loading