



FASCO® F3 90-40



TOOL FEATURES

- Designed for industrial use, powerful and fast
- Easy to use
- Top-loading magazine
- Switch trigger for single and contact actuation
- Depth adjustment

MEDIUM WIRE STAPLES

- Up to 40 mm (1 5/8") leg length
- With different point options available
- Are available in different materials



CONTACT & SERVICE

**Our sales team
is available at:**

P +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

These fast and powerful pneumatic staplers are designed for industrial use and offer reliable performance and intuitive operation. They feature a top-loading magazine for quick reloading, a fast jam removal system, and ergonomic handling. The switch trigger gives the possibility to change easily from single operation to contact actuation.

APPLICATIONS

- Furniture and frame assembly
- Carpentry
- Panels and boards
- Prefabricated houses
- Wooden packaging

HANDLING

1. Load staples from the top into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
237 mm	72 mm
9.34 inch	2.84 inch
Length	Weight
294 mm	1,59 kg
11.60 inch	3.50 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

0.341 L. | 0.014 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Outside Crown	5.70 mm 0.22"
Inside Crown	3.20 mm 0.13"
Diameter	1.00 x 1.25 mm 0.039 x 0.049"
Length	12 - 40 mm 1/2 - 1 5/8"
Magazine Capacity	158
Staple Type	BECK 90, ATRO® 90, BEA® 90, DUOFAST® 18, HAUBOLD® 6000, HOLZHER® C, PREBENA® E, PREBENA® ES1, SENCO® L, SENCO® N4450

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 99.30 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 92.40 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit
set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:

Single Sequential Actuation,
Contact Actuation

Loading: Top Loading

