



FASCO® F3 92-40



## TOOL FEATURES

- Designed for industrial use, powerful and fast
- Easy to use
- Top-loading magazine
- Depth adjustment
- Two triggers available: Single Sequential and Contact Actuation

## MEDIUM WIRE STAPLES

- Up to 40 mm (1 5/8") leg length
- With different point options available
- Are available in different materials



## CONTACT & SERVICE

Our sales team is happy to assist you:

P +1 800 239 8665  
sales@beck-america.com  
www.beck-america.com

## DESCRIPTION

These fast and powerful pneumatic staplers are designed for industrial use and offer reliable performance and intuitive operation. They feature a top-loading magazine for quick reloading, a fast jam removal system, and ergonomic handling. Two trigger options are available. Two trigger options are available: assembled on the tool is a single sequential trigger, the second trigger for contact actuation is packed in the box.

# FASCO® F3 92-40

## APPLICATIONS

- Furniture and frame assembly
- Carpentry
- Panels and boards
- Prefabricated houses
- Wooden packaging

## HANDLING

1. Load staples from the top into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

| Height     | Width     |
|------------|-----------|
| 237 mm     | 72 mm     |
| 9.33 inch  | 2.84 inch |
| Length     | Weight    |
| 309 mm     | 1,60 kg   |
| 12.18 inch | 3.53 lbs  |

### Pressure

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

0.341 L. | 0.014 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

|                   |                                    |
|-------------------|------------------------------------|
| Outside Crown     | 8.90 mm   0.350"                   |
| Inside Crown      | 6.40 mm   0.252"                   |
| Diameter          | 1.00 x 1.25 mm  <br>0.039 x 0.049" |
| Length            | 12 - 40 mm  <br>1/2 - 1 5/8"       |
| Magazine Capacity | 175                                |
| Staple Type       | BECK 92<br>BEA® 92,<br>HOLZHER E   |

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 99.30 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 92.40 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit  
set by UNI EN ISO 12100-1/2

## ACTUATION & LOADING

Actuation System:

Single Sequential Actuation,  
Contact Actuation

Loading: Top Loading

