



F33 CN15W-PS50 SCR



TOOL FEATURES

- Compatible with Mini-Sheet Coil SCRAIL® fasteners
- Toothed safety yoke for toe-nailing
- Includes a sequential fire / bump fire (Single Shot / Contact Trip) selector

SCRAIL®

- Twice as fast to use than collated screws
- Eight times faster to use than bulk screws
- Can be used for almost all screw applications
- Easily installed, quickly removed
- Dramatically increased holding power versus nails



CONTACT & SERVICE

Our sales team is available at:

P +43 7724 2111-671
sales.us@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

- Easy to handle thanks to its light weight and good balance
- Rubber comfort grip and adjustable exhaust
- Tough adjustable safety yoke and body design

BECK AMERICA

105 Industrial Park Drive
35661 Muscle Shoals, Alabama | USA
P +1 800 239 8665 | F +1 256 381 6659
E sales.us@beck-fastening.com | W www.beck-fastening.com

Follow us



F33 CN15W-PS50 SCR

APPLICATIONS

- Siding
- Fencing
- Pallets
- Kitchen units
- Sheathing
- Trade shows

HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
290 mm	110 mm
11.42 inch	4.33 inch
Length	Weight
263 mm	1.87 kg
10.35 inch	4.12 lbs

Pressure

5 - 7 bar | 70 - 100 psi

Air consumption per shot

0.75 L. | 0.026 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 96.30 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 90.60 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.5 m/s²

ACTUATION & LOADING

Actuation System: Single Shot
& Contact Actuation

Loading: Coil

VARIATIONS

F44AC CN15W-PS65 SCR

FASTENER DATA NAILS

	Wire	Plastic
Diameter	1.60 - 2.50 mm 0.063 - 0.098"	
Shank	smooth ring screw	
Pitch	6 - 7 mm 0.236 - 0.275"	6mm 0.236"
Head	3.5 - 5 mm 0.138 - 0.197"	
Length	22 - 50 mm 7/8 - 2"	
Magazine Capacity	200 - 400	
Nail Type	15° Wire Coil Nails Mini-Sheet Coil Nails (CN-AG)	

FASTENER DATA SCRAIL®

	Wire	Plastic
Diameter	1.70 - 2.30 mm 0.067 - 0.090"	
Head	Phillips® Pozi Torx®/Star	
Length	22 - 50 mm 7/8 - 2"	
Pitch	6 - 7 mm 0.236 - 0.275"	6mm 0.236"
Magazine Capacity	300	
SCRAIL® Type	15° Mini-Sheet Coil SCRAIL®	

Changes and errors excepted. All rights reserved.

SCRAIL® is a registered trademark of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (PoziDrive®) are all trademarks of their respective owners.

VERSION
01/2022 US