



## F44AC CN15-PS35 HAFTEN



### TOOL FEATURES

- Easy to handle thanks to its light weight and good balance
- Includes switchable trigger for full sequential fire and bump fire
- Tool-free depth of drive adjustment

### 15° PLASTIC SHEET HAFTEN NAILS

- Special ring nails in order to fix the guide clips of metal roofs
- Available in standard steel, stainless steel A2 & A4 and high strength steel
- Also available in electro galvanized



### CONTACT & SERVICE

**Our sales team  
is available at:**

T +43 7724 2111-671  
[sales@beck-fastening.com](mailto:sales@beck-fastening.com)  
[www.beck-fastening.com](http://www.beck-fastening.com)

### DESCRIPTION

- Drives 15° plastic sheet coil haften nails
- Fully pneumatic feeding and positioning system allows precise nailing
- Rubber comfort grip and adjustable exhaust
- Belt hook
- Removable no mar tip

# F44AC CN15-PS35 HAFTEN

## APPLICATIONS

- Coverings
- Zinc Sheathing
- Tin Roofs

## HANDLING

1. Load the coil in the magazine
2. Position first nail in nose channel and align top of nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

Height	Width
322 mm	130 mm
12.67 inch	5.12 inch
Length	Weight
275 mm	2.40 kg
10.82 inch	5.29 lbs

### Pressure

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

1.20 L. | 0.042 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

<b>Diameter</b>	2.50 mm   0.098"
<b>Head</b>	6.80 mm   0.268"
<b>Pitch</b>	7.50 mm   0.295"
<b>Length</b>	25 - 35 mm   1 - 1 3/8"
<b>Capacity</b>	200 nails
<b>Nail Type</b>	15° Plastic Sheet Haften Nails

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 92.02 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 81.50 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System: Single shot &  
contact actuation

Loading: Coil

