



**F44AC CN15-PS65  
DRYWALL-AFTEN**



**TOOL  
FEATURES**

- Easy to handle thanks to its light weight and good balance
- Includes switchable trigger for full sequential actuation and contact actuation
- Tool-free depth of drive adjustment

**15° PLASTIC SHEET  
DRYWALL NAILS**

- Ideal for fastening of plasterboards and gypsum fibre boards
- Ringed shank for superior holding power
- Concave cupped head for a smooth surface of the drywall after spackle and sanding

**15° PLASTIC SHEET  
HAFTEN NAILS**

- Special ring nails in order to fix the guide clips of metal roofs
- Available in standard steel, stainless steel A2 & A4 and high strength steel
- Also available in electro galvanized

**DESCRIPTION**

Whether for roofing or for drywall fastening, the FASCO® F44AC CN15W-PS65 DRYWALL-HAFTEN coil nailer perfectly processes both 15 ° plastic sheet coil drywall nails and haften nails. The nailer's fully pneumatic feeding and special positioning system allow the nails to be set with extreme precision. Play it safe with the removable no-mar tip, to avoid damages to the surface.

**BECK AMERICA**

105 Industrial Park Drive  
35661 Muscle Shoals, Alabama | USA  
P +1 800 239 8665 | F +1 256 381 6659  
E sales.us@beck-fastening.com | W www.beck-fastening.com

# F44AC CN15W-PS65 DRYWALL-HAFTEN

## APPLICATIONS

- Drywall
- Gypsum Wall Board
- Coverings
- Zinc Sheathing
- Tin Roofs

## HANDLING

1. Load the coil in the magazine
2. Position first nail in nose channel and align top of nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

Height	Width
322 mm	130 mm
12.67 inch	5.12 inch
Length	Weight
275 mm	2.40 kg
10.82 inch	5.29 lbs

### Pressure

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

1.20 L. | 0.042 SCF  
Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

<b>Diameter</b>	2.50 mm   0.099"
<b>Head</b>	6.80 mm   0.268"
<b>Pitch</b>	7.50 mm   0.295"
<b>Length</b>	25 - 65 mm   1 - 2 1/2"
<b>Capacity</b>	200 nails
<b>Nail Type</b>	15° Plastic Sheet Drywall Nails, 15° Plastic Sheet Haften Nails,

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 92.02 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 81.50 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:  
Full sequential actuation &  
contact actuation

Loading: Coil

