



## F44AC CN15W- PS65 SCR



### TOOL FEATURES

- Suitable for nails & SCRAIL®
- Switchable trigger for single shot and bump fire
- Tool-free depth of drive adjustment

### SCRAIL®

- Twice as fast to use than collated screws
- Eight times faster to use than bulk screws
- Can be used for almost all screw applications
- Easily installed, quickly removed
- Dramatically increased holding power versus nails



### CONTACT & SERVICE

Our sales team  
is available at:

P +1 800 239 8665  
sales@beck-america.com  
www.beck-america.com

### DESCRIPTION

- Easy to handle thanks to its light weight and good balance
- Drives both wire welded and plastic sheet coil nails and SCRAIL®
- Fully pneumatic feeding and positioning system allows precise nailing
- Rubber comfort grip and adjustable exhaust
- Removable no mar tip

# F44AC CN15W-PS65 SCR

## APPLICATIONS

- Siding
- Fencing
- Subflooring
- Decking
- Roof joists
- Garden furniture
- Boxes and crates

## HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

Height	Width
322 mm	130 mm
12.67 inch	5.12 inch
Length	Weight
275 mm	2,40 kg
10.82 inch	5.29 lbs

### Pressure

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

1.20 L. | 0.042 SCF

Performance at 90 psi | 6.2 bar (0.62 MPa)

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 92.02 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 81.50 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System: Single Shot & Contact Actuation

Loading: Coil

## VARIATIONS

F44AC CN15W-PS65

## FASTENER DATA NAILS

	Wire	Plastic
<b>Diameter</b>	2.30 - 2.80 mm   0.091 - 0.110"	
<b>Shank</b>	smooth   ring   screw   knurled	
<b>Pitch</b>	7 - 8 mm   0.275 - 0.314"	7.50 mm   0.295"
<b>Head</b>	5 - 7 mm   0.197 - 0.275"	
<b>Length</b>	25 - 65 mm   1 - 2 1/2"	
<b>Magazine Capacity</b>	250 - 400	200
<b>Nail Type</b>	15° Wire Coil Nails 15° Plastic Sheet Coil Nails (CN-AG)	

## FASTENER DATA SCRAIL®

<b>Diameter</b>	2.50 - 3.50 mm   0.098 - 0.138"
<b>Head</b>	Phillips®   Pozi   Torx®/Star   Versa
<b>Length</b>	30 - 57 mm   3/16 - 2 1/4"
<b>Magazine Capacity</b>	200 - 300
<b>SCRAIL® Type</b>	15° Wire Coil SCRAIL®   15° Plastic Sheet Coil SCRAIL® (CN-AG)

Changes and errors excepted. All rights reserved.

SCRAIL® is a registered trademark of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (PoziDrive®) are all trademarks of their respective owners.

**VERSION**  
**01/2021 US**