



**F44AC CN15W-
PS65 SCR**

TOOL FEATURES

- Suitable for nails & SCRAIL®
- Switchable trigger for single shot and bump fire
- Tool-free depth of drive adjustment

SCRAIL®

- Twice as fast to use than collated screws
- Eight times faster to use than bulk screws
- Can be used for almost all screw applications
- Easily installed, quickly removed
- Dramatically increased holding power versus nails



CONTACT & SERVICE

**Our sales team
is available at:**

P +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

- Easy to handle thanks to its light weight and good balance
- Drives both wire welded and plastic sheet coil nails and SCRAIL®
- Fully pneumatic feeding and positioning system allows precise nailing
- Rubber comfort grip and adjustable exhaust
- Removable no mar tip

F44AC CN15W-PS65 SCR

APPLICATIONS

- Siding
- Fencing
- Subflooring
- Decking
- Roof joists
- Garden furniture
- Boxes and crates

HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
322 mm	130 mm
12.67 inch	5.12 inch
Length	Weight
275 mm	2,40 kg
10.82 inch	5.29 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

1.20 L. | 0.042 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 81.50 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s²

ACTUATION & LOADING

Actuation System: Single Shot
& Contact Actuation

Loading: Coil

VARIATIONS

F44AC CN15W-PS65

FASTENER DATA

NAILS

	Wire	Plastic
Diameter	2.30 - 2.80 mm 0.091 - 0.110"	
Shank	smooth ring screw knurled	
Pitch	7 - 8 mm 0.275 - 0.314"	7.50 mm 0.295"
Head	5 - 7 mm 0.197 - 0.275"	
Length	25 - 65 mm 1 - 2 ½"	
Magazine Capacity	250 - 400	200
Nail Type	15° Wire Coil Nails 15° Plastic Sheet Coil Nails (CN-AG)	

FASTENER DATA

SCRAIL®

Diameter	2.50 - 3.50 mm 0.098 - 0.138"
Head	Phillips® Pozi Torx®/Star Versa
Length	30 - 57 mm ¾ - 2 ¼"
Magazine Capacity	200 - 300
SCRAIL® Type	15° Wire Coil SCRAIL® 15° Plastic Sheet Coil SCRAIL® (CN-AG)

Changes and errors excepted. All rights reserved.

SCRAIL® is a registered trademark of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (PoziDrive®) are all trademarks of their respective owners.

VERSION
01/2021 EN