



F44AC G-50 TL



TRANSITION PERIOD: Product branding changes according to the new brand design.

**TOOL-
FEATURES**

- Design protected by copyright with good ergonomics
- Tool-free jam clearing mechanism provides an easy access to the nose if the staple jams
- Opening bar on magazine facilitates staple loading

**HEAVY DUTY
STAPLES**

- Fast processing
- Point geometry adjusted to the particular application
- For connecting drywall panel joints



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- Limited recoil resulting from balanced weight distribution
- Multi-directional exhaust
- Includes a sequential fire / bump fire (single shot / contact actuation) device
- Depth control dial for precise countersinking
- Solid and durable design for the most demanding jobs

APPLICATIONS

- Sheathing
- Subflooring
- Roof decking
- Furniture frames
- Pallets
- Vinyl siding
- Crates
- Box assembly

HANDLING

1. Load fastener from the top into the magazine
2. Connect air supply
3. Avoid a dry and dirty tool by cleaning and lubricating regularly

TOOL CHARACTERISTICS

Height	Width
310 mm	92 mm
12.20 inch	3.62 inch
Length	Weight
345 mm	2,25 kg
13.58 inch	4.95 lbs

Pressure

5 - 7 bar | 70 - 100 psi

Air consumption per shot

1.16 L. | 0.041 SCF
Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Outside Crown	11,10 mm 0.437"
Inside Crown	7,60 mm 0.299"
Diameter	1,40 - 1,60 mm 0.055 - 0.062"
Length	25 - 50 mm 1 - 2"
Magazine Capacity	155
Staple Type	SENCO® G5562 (=N), ATRO® 100, BEA® 14/155, Haubold® KG700

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 81.50 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s²

ACTUATION & LOADING

Actuation System: Single shot & contact actuation

Loading: Top Loading

VARIATIONS

- F47C B7/G-65 STAPLER

FURTHER INFORMATION

Also available with ETA certification.

