



**F70G RHN20-90**  
**SCRAIL®**



## TOOL FEATURES

- Powerful cordless tool for 17° and 20° plastic strip SCRAIL® and nails
- Tool-free depth of drive adjustment
- Rubber comfort grip ensures a non-slip handling

## SCRAIL® SUBLOC® PRO

- Aggressive double threads for squeakless subfloors
- DIAMOND COATING for maximum holding power
- Material: standard steel, SS304/A2 stainless steel
- Finish: electro-galvanized, FasCoat®

## DECKING SCRAIL®

- Fine Thread SCRAIL® with a blunt “splitless” diamond point
- DIAMOND COATING for maximum holding power
- Optimized to work flawlessly in various wood species, e.g. soft wood like spruce and SYP
- Material: stainless steel A2 & A4, FasCoat®

## DESCRIPTION

- Belt hook
- Full Sequential Actuation
- Works with Fasco® fuel cells
- Powerful NiMh battery
- Lights indicate battery charge

## CONTACT & SERVICE

**Our sales team is available at:**

P +1 800 239 8665  
sales@beck-america.com  
www.beck-america.com

### BECK AMERICA

105 Industrial Park Drive  
35661 Muscle Shoals, Alabama | USA  
P +1 800 239 8665 | F +1 256 381 6659  
sales@beck-america.com | www.beck-america.com

# F70G RHN20-90 SCR

## APPLICATIONS

- Subflooring
- Decking
- Hiking trails
- Boardwalks
- Docks
- Siding
- Fencing
- Outdoor furniture

## HANDLING

1. Load fuel cell
2. Load fastener from the rear into the magazine
3. Connect battery
4. Clean and maintain gas tool regularly

## TOOL CHARACTERISTICS

| Height     | Width     |
|------------|-----------|
| 375 mm     | 108 mm    |
| 14.76 inch | 4.25 inch |
| Length     | Weight    |
| 366 mm     | 3.53 kg   |
| 14.41 inch | 7.77 lbs  |

### Shot limit

1000 Shots / hour

### Speed

2-3 Shots / second

**Gas type** Liquid petroleum gas

### Operating temperature

-7 / 49° C | 19 / 120° F

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 100.20 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 97.20 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

5.26 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:

Full Sequential Actuation

Loading:

Rear Loading

## BATTERY

### Input Charge

220-240 VAC 50 Hz

### Charge Time

1 Hour

### Capacity

1650 mAh

### Voltage

6 VDC

### Shot / Battery

Max. 5200

### Shot / Fuel Cell

Max. 1200

## FASTENER DATA NAILS

|           |                                                       |
|-----------|-------------------------------------------------------|
| Diameter  | 2.9 - 3.8 mm   0.114 - 0.148"                         |
| Shank     | smooth   ring   screw  <br>barbed   twisted   knurled |
| Head      | 7.0 mm   0.275"                                       |
| Length    | 50 - 90 mm   2 - 3 1/2"                               |
| Capacity  | 32                                                    |
| Nail Type | 17° + 20° Plastic Strip Nails                         |

## FASTENER DATA SCRAIL®

|              |                                                                |
|--------------|----------------------------------------------------------------|
| Diameter     | 2.80 - 3.50 mm   0.113 - 0.138"                                |
| Head         | Torx®/Star   Versa   Square  <br>Phillips®   Pozi (Pozidrive®) |
| Length       | 50 - 75 mm   2 - 3"                                            |
| Capacity     | 32                                                             |
| SCRAIL® Type | 17° + 20° Plastic Strip SCRAIL®                                |

Changes and errors excepted. All rights reserved.

FASCO®, SCRAIL®, SUBLOC® and FasCoat® are registered trademarks of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (Pozidrive®) are all trademarks of their respective owners.

**VERSION**  
**10/2020 US**