



## CORDLESS STRIP NAILER 3 1/2" 30 - 34 DEGREE FSN33-90 BC



### MANY BRANDS ONE BATTERY SYSTEM

This product is compatible with all 18 V battery packs and chargers within the CAS system.

[cordless-alliance-system.com](http://cordless-alliance-system.com)

### BENEFITS FOR PROFESSIONALS

- + Precise fastening with high driving power
- + Tool-free depth adjustment
- + Belt hook for convenient carrying
- + Dry Fire Lock
- + No cables, no hoses – complete freedom of movement
- + No gas, no follow-up costs
- + Low maintenance
- + Firing speed of 3 shots per second for efficient operation



### DESCRIPTION

The BECK 30 - 34° Cordless Framing Nailer combines the full power of a pneumatic nailer with the freedom of cordless hand tools. Ideal for demanding applications in timber and interior construction, it enables fast, powerful, and precise fastening with maximum freedom of movement. Its robust design, high driving power, and compatibility with CAS batteries make it a reliable tool for professional craftsmen who value performance, flexibility, and efficiency.

### CONTACT & SERVICE

Our customer service is happy to assist you.

P +1 800 239 8665 | F +1 256 381 6659  
[sales.us@beck-fastening.com](mailto:sales.us@beck-fastening.com)  
[beck-fastening.com](http://beck-fastening.com)

**BECK AMERICA**  
105 Industrial Drive  
Muscle Shoals, AL  
35661 | USA

Follow us



## TOOL SPECIFICATIONS

MAGAZINE TYPE	Strips
MAGAZINE CAPACITY	57 Nails
BATTERY COMPATIBILITY	CAS 18 V LiHD 4.0 Ah
SHOTS / SECOND	2 – 3
SHOTS / BATTERY CAPACITY	600 (4 Ah)
ACTUATION SYSTEM	Single Sequential Actuation
BATTERY VOLTAGE	18 V
FASTENER TYPE	33° Paper Tape Clipped and Full Offset Round Head Nails, 33° Plastic Strip Nails
LOADING	Rear Loading
DEPTH ADJUSTMENT	Yes
BELT HOOK	Yes
INCLUDED	Tool, CAS Battery, Charger, Belt Hook, and Carrying Case
WEIGHT	9.85 lbs   4.47 kg

## FASTENER CHARACTERISTICS

FASTENER TYPE	33° Paper Tape Clipped and Full Offset Round Head Nails, 33° Plastic Strip Nails
WIRE	0.113" – 0.131"   2.90 x 3.30 mm
HEAD	0.263" – 0.293"   6.68 – 7.44 mm
LENGTH	2" – 3 1/2"   50 – 90 mm



### APPLICATIONS

- + Framing
- + Deck Construction
- + Sheathing
- + Crate and pallet construction
- + Flooring and subflooring

### HANDLING

1. Insert nail strip into the back of the magazine
2. Slide the nail strip forward in the magazine
3. Pull the pusher back to engage the nail feeder to the nail strip
4. Slide the battery in the tool's handle until it is firmly seated
5. Press the power switch button to switch on the tool